

Trójnik PVC-U 90° d 25



Cena brutto	5,04 zł
Cena netto	4,10 zł
Numer katalogowy	P 504 00 025 2
Producent	Pimtas

Opis produktu

Trójnik 90o d 25 PVC-U - kształtka stosowana do budowy instalacji ciśnieniowych w fabrykach.

Kształtka **trójnik d 25 PCV 90 stopni** jest odporna na działanie kwasów i zasad .

Dane techniczne

d(mm)	DN	L(mm)	Z(mm)	Kg/Pie	Pcs / Box	PN
20	15	16,0	11,0	0,028	400	16
25	20	18,5	14,0	0,040	250	16
32	25	22,0	18,0	0,070	140	16
40	32	26,6	23,0	0,116	75	16
50	40	31,0	28,0	0,225	45	16
63	50	38,0	34,0	0,348	40	16
75	65	44,7	40,0	0,558	25	16
90	80	51,0	46,0	0,924	18	16
110	100	61,0	55,0	1,444	9	16
125	110	69,0	67,0	2,092	6	16
140	125	76,0	71,0	2,180	4	16
160	150	86,0	86,0	3,302	4	16
200	175	106,0	101,0	4,572	2	10
225	200	118,0	114,0	4,966	1	10
250	250	131,0	132,0	8,920	1	10
280	250	146,0	152,0	11,300	1	10
315	300	163,0	168,0	16,450	1	10
355	350	193,0	196,0	23,625	1	10
400	400	216,0	214,0	28,187	1	10